

MAXICHARGER DC FAST

DC Charger

Experience the future of electric vehicle charging with the MaxiCharger DC Fast. This powerful charger redefines fast charging, providing unparalleled efficiency and reliability for EV owners and operators.

DC Output Connection

Charging Mode	Mode 4: CCS2
Output Power	60kW/120kW/180kW/240kW
Output Voltage	CCS2: Standard: 200A; Optional 300A (Nominal), 400A (Peak) CHAdeMO: 125A or 200A
Number of Outputs	2*CCS2, or 1*CCS2+1*CHAdeMO; 1*AC socket (Optional)
Peak Efficiency	≥96%

AC Input Connection

Earthing System	3P, N, PE
Input Voltage	3-phase 400V AC f10%
Input Frequency	50Hz
Power Factor	≥0.99
Harmonic distortion (THDi)	≥5%

General Characteristics

IP and IK Rating	IP54; IK10
Operating Altitude	2000m
Operating Temperature Range	-35°C~+55°C
Storage Temperature Range	-40°C~+70°C
Mounting	Floor Standing
Dimensions (H x W x D)	1950h820h600mm (60kW/120kW) 1950h820h700mm (180kW/240kW)
Screen Type	27 inch LCD Touch Screen (1920*1080)
Cable Length	4m standard; 5m, 6.5m or 7m optional

User Interface

Status Indication	LED/LCD/APP
User Interface	Autel Charge APP Autel Charge Cloud
Connectivity	4G, Wi-Fi, Ethernet
Communication Protocols	OCPP 1.6J (Can be Upgraded to OCPP 2.0.1 Later)
User Authentication	APP, RFID Card, Credit card (Optional)

Certification and Specifications

Safety and Compliance	IEC 61851-23 IEC 61851-21-2 ISO 15118
Certification	CE, EMC Class A, Eichrechtskonform (Optional)
Warranty	24 months Warranty Extension Possible

Software Update

Software Update	OTA Updates via Web Portal
-----------------	----------------------------



joltie

Joltie Hellas
Chimarras 5, 15125, Marousi, Attica, Greece
Tel.: +30 210 3242020, Fax: +30 210 3242023
Production Unit: Evnikis 10, 19600, Mandra, Attica, Greece
info@eunice-group.com
www.eunice-group.com