

# Joltie Box T

Introducing the Joltie Box Home car charger, designed for private parking spaces. With a built-in 5m charging cable with AC Type 2 connectivity (7.4kW single phase, 22kW three phase), it offers efficient and easy charging for any vehicle. With an IP55 and IK08 protection rating, it ensures safety and durability, making it the ideal home charging solution.



## General Specifications

	Single-Phase	Three-Phase
Charging Mode	Mode 3	
Cable Length Type 2	5m	
Dimensions without Cable	356 x 200 x 110 mm	
Weight	~ 5 Kg	~ 6 Kg

## Electrical Specifications

	Single-Phase	Three-Phase
Maximum Current	Adjustable from 6,5 A to 32 A	
Maximum Power	Adjustable from 1,5kW to 7,4kW	Adjustable from 4,5kW to 22,2kW
Power Supply	230 V $\pm$ 10% 50-60 Hz	400 V $\pm$ 10% 50-60 Hz
Network Configuration	TT / TN	

## Connectivity

	Single-Phase	Three-Phase
Internet Protocol Interoperability	OCPP 1.6 Json	
Interfacing with Management Systems	Modbus RTU RS485	

## Features

	Single-Phase	Three-Phase
Status Indication & Messages	Matrix LED Screen	
User & Administrator Management	Via App	
Locking, Unlocking hourly Scedulling Lock	Via App	

## Safety

	Single-Phase	Three-Phase
DC Current Sensing (RCM)	Intergrated, 6 mA CC (Allows use of RCD type A)	

## Environmental Resistance

	Single-Phase	Three-Phase
IP Rating	IP55	
IK Degree of Protection	IK10	
Operating Temperature	From -25 C to +55 C	
Enclosure Material	High Resistance PC + ASA	

## Certification

	Single-Phase	Three-Phase
Cartification	CE	
International Reference Standard	IEC 61851-1, IEC 61851-21, IEC 62196-2	

# joltie

Joltie Hellas  
Chimarras 5, 15125, Marousi, Attica, Greece  
Tel.: +30 210 3242020, Fax: +30 210 3242023  
Production Unit: Evnikis 10, 19600, Mandra, Attica, Greece  
[info@eunice-group.com](mailto:info@eunice-group.com)  
[www.eunice-group.com](http://www.eunice-group.com)